

FUJIFILM FCR PRIMA T2

This compact table-top reader unit has outstandingly high-speed processing capability to challenge the common misconception of CR



**Product description:**

**High-speed processing**

FCR PRIMA T2 is a table-top reader unit which boasts a world-class high processing speed of 73 IPs/hour. In the high speed mode (5 pixels/mm), throughput is enhanced almost 70% compared with FCR PRIMA T (only for IPs of 14" x 17" and 14" x 14"). As with all Fujifilm equipment FCR PRIMA T2 is easy to operate. It will help reduce patient waiting time and greatly increase the efficiency of examination workflow.

**Space-saving design**

FCR PRIMA T2, with its light and compact table top design, can be placed on a desk, shelf or anywhere space is limited. As this is a fully digital reader, neither a darkroom nor automatic processor is required. FCR PRIMA T2 can always be installed in the space formally used by a chemistry based processor.

**Stable high-quality images**

Although this is a compact machine its excellent image quality is the same as that produced by the rest of the FCR range. Image Intelligence™, Fujifilm's proprietary image processing technology, enhances image contrast and sharpness, without any deterioration of details. FCR PRIMA T2 supports accurate diagnosis by offering stable and optimized image quality.

**Specifications**

Standard components	FCR PRIMA T2 Image reader (Model : CR-IR 392)
Applicable console	FCR PRIMA T2 Console, FCR View; CR Console, Console Advance
Main Connectable Imagers	DryPix PRIMA/Smart/Lite/Plus/4000

Supplies	<p>Plaque d'imagerie ST-VI:            35 x 43 cm (14 "x 17"), 35 x 35 cm (14 "x 14"), 10 "x 12", 8 "x 10", 24 x 30 cm, 18 x 24 cm, 15 x 30 cm            Type de cassette IP CC: 35 x 43 cm (14 "x 17"), 35 x 35 cm (14 "x 14"), 10 "x 12", 8 "x 10", 24 x 30 cm, 18 x 24 cm, 15 x 30 cm</p>
Time required for IP Feed/Load	Min. 49 sec.
Processing capacity	Up to 73 IPs/hr
Reading specification	10 pixels / mm, 5 pixels / mm
Time to start on display	Min. 33 sec.
Time to print on DryPix Prima	Approx. 165 sec. (Approx. 155 s) * in case of 35 x 43 cm (14 "17")
Number of stacker	1
Network	10 Base T / 100 Base TX
Dimensions (W x D x H)	560 x 540 x 392 mm (22" x 21" x 15")
Weight	39 kg (86 lbs.)
Power supply conditions	Single phase 50-60 Hz AC120 - 240 V +-10% 1.9A (max)
Environnemental conditions	<p>Operating conditions</p> <ul style="list-style-type: none"> <li>• Temperature: 15-30 ° C</li> <li>• Humidity: 15 to 80% HR (no dew condensation)</li> <li>• Atmospheric pressure: 750-1060hPa</li> </ul>

Reference: -