

BARCO NIO FUSION 12MP MDNC-12130
Diagnostic versatility at your fingertips



Product description:

- Multimodality display for PACS and breast imaging
- 12MP screen resolution and Uniform Luminance Technology
- Accurate and consistent colors and greyscales
- Integrated tools to support workflow and improve ergonomics
- Automated QA and compliance tests

A versatile diagnostic display, for both PACS and breast imaging

The Nio Fusion 12MP (MDNC-12130) display is designed to combine PACS and breast images on one workstation, so you don't need to work on a cluttered desk with complex configurations and multiple portrait displays. A Nio Fusion 12MP will represent both 2D and 3D images fluidly, brightly and in detail, further helping you to speed up your reading sessions. A set of unique integrated clinical tools improve reading ergonomics and support efficient workflow for static and dynamic imaging.

- Medical grade display
- Excellent uniformity correction
- Perfect representation of calibrated colors and greyscales

Enjoy consistent and compliant colors and greyscales

With a 12 MegaPixel resolution, you'll fit multiple images on one screen and enjoy every single one in extremely sharp and precise quality, with less panning and zooming. Nio Fusion 12MP displays are calibrated to meet the DICOM standard for greyscales. And thanks to the SteadyColor™ technology, you can also confidently rely on perceptually linear colors.

Barco's QAWeb Enterprise software, included in the display, guarantees consistent image quality calibration and QA, and also enables compliance to the latest regional and international regulations for image quality.

Read on a flexible display, with optimal comfort

The Nio Fusion 12MP is surprisingly thin and light. It mirrors most of a human's natural field of vision and was designed to reduce head, hand and eye movements to a minimum. You can even switch between two workstations in no time, at the touch of a button with integrated KVM (Keyboard-Video-Mouse).

- Reflection-free surface enhances image sharpness
- SoftGlow™ ambient lighting reduces eye fatigue
- Uniform Luminance Technology ensures constant luminance in all regions of the screen
- Ambient Light Sensor and Compensation provide consistent images in any lighting conditions

A future-proof investment that lasts

The Nio Fusion 12MP is an all-in-one imaging solution, for both PACS and breast imaging, which will make it possible for you to save operational costs. Its smooth, fast system was designed to support you in your workflow, enabling you to see more patients. And last but not least, thanks to its long lifetime, the display can be your companion for years to come. All its components are warranted for 5 years

Caractéristiques

Technologies that enhance image quality:

- Uniform Luminance Technology to ensure that all regions of the screen have an even luminance
- SteadyColor™ calibration technology to meet the DICOM standard for grayscales and to guarantee consistent, perceptually linear color
- SteadyGray™ ensures that all gray values closely match the selected white tint. This can be blue base, clear base, or some other preferred white tint
- QAWeb Enterprise, a cloud-based technology for automated calibration and Quality Assurance
- I-Guard™ front sensor to ensure 24/7 compliance to medical standards
- Efficient DuraLight™ backlights for a long lifetime of brighter images

Technologies that enhance productivity:

- RapidFrame™ to ensure crisp and in-focus moving images, with up to 10% higher detection of small details in moving images*
- Conference CloneView™ software to project and control images on a large screen with ease
- SoftGlow™ task and wall lighting to improve reading room conditions
- SpotView™ to highlight subtle details in a region of interest
- KVM to switch effortlessly between two workstations

Features

- Active screen size (diagonal) : 784 mm (30.9")
- Active screen size (H x V) : 653 x 435 mm (25.7 x 17.1")
- Aspect ratio (H:V) : 3:2
- Resolution Native : 12MP (4200 x 2800 pixels), configurable to 2 x 5.8MP (2100 x 2800 pixels)
- Maximum luminance (panel typical) : 1200 cd/m²
- DICOM calibrated luminance : 600 cd/m²
- Response time ((Tr + Tf)/2) (typical) : 10 ms (average, with all single transitions within 1 frame period)

PRODUCT SHEET

Megapixels: 12MP

Reference: -